
BioHarness Zephyr Physiological Status Monitoring (PSM) System

9361 Winkler Drive, Suite A Houston, TX 77017 Phone: 713.947.6469 Fax: 713.947.6488

BioHarness Zephyr Physiological Status Monitoring (PSM) System



Designed To Make Montioring Wireless


genuine remote monitoring of human performance and condition in the real world transmission of comprehensive physiological data on the wearer via mobile and fixed data networks - enabling The BioHarness™ 3 is the premiere compact physiological monitoring module that enables the capture and

sectors, including academic and research, sports, defense and wellness. including research, training and wellness situations. It offers a vital advantage to users in a diverse range of BioHarness 3 has applications in any field requiring high-level wireless and remote physiological monitoring.

⊠ Edelhoff Technologies USA


TI	Features	Bio	BioHarness Spe	ecifications
	 Multiple Physiological Measurements 	ical Measurements	HR Range:	25 - 240 BPM
	 Heart Rate 		BR Range:	4-70 BPM
	 Heart Rate Variability 	'ariability	Acc. Range:	±16g
	 Heart Rate Recovery 	Recovery	Battery Type:	Rechargeable Lithium
	 Respiration Rate 	Rate		Polymer
	 Accelerometry 	Ŋ	Battery Life:	26 Hours per charge
	 Intensity & Load 	oad	Charge Cycles:	300
	 Estimated Co 	Estimated Core Temperature	Transmit Range:	To ~300ft,
	 and more! 			~1000ft w/Antenna &
	- I ha Training Zone	Š		Amplifier
	 Live Iraining Zones 	Ĭ,	Frequency:	2.4 - 2.4835GHz
	 Individual and Team Reporting 	ım Reporting	Garment Washes:	80
			Operating Limits:	
	Available Leam Cr	Available Leam Compression shirts make monitoring	Temperature:	-10 60°C
·	comforatble and easy	asy	Humidity:	5 – 95%
	 Designed to monit 	Designed to monitor 50+ people simultaneously	_	


BioHarness Zephyr Physiological Status Monitoring (PSM) System



⊠ Edelhoff Technologies USA


٠






- Blue Bluetooth indicator LED Orange battery indicator LED Red HR detection status LED
- Green logging indicator LED ON/OFF button


- 6. Ground spring contact
 7. Rear label location
 8. ECG signal spring contact
 9. USB charging/configuration contacts
 10. Breathing signal spring contact



- Main fastener sleeve
- Wash, size and serial # label
- Loop for optional shoulder strap
- Zephyr brand label
- BioHarness module receptacle and sensor contacts
- Ģ Size adjustment slider buckle

- 7. Main fastener hook
- Internal breathing sensor location
 Conductive ECG sensor pad
 Conductive ECG sensor pad






- 7. Configurable field 2
- 8. Configurable field 3
- 9. Data age indication (4 x 1min quadrants) if Status = Blue
- 10. Configurable field 4

- 16. Red cross means BioGauge also displayed on Medic Tab (not visible)
- 17. Activity Level (†) = walking equivalent ((†)) = rurning equivalent
- 18. ? = posture indication

BioHarness Zephyr Physiological Status Monitoring (PSM) System




ECHO Gateway


Connects to PC to link PSM monitor to PC/monitoring software

BioHarness Zephyr Physiological Status Monitoring (PSM) System

ECHO Repeater

Signal range extender





≅ Edelhoff Technologies USA